

**LINEAR TECHNOLOGY MATERIALS DECLARATION**

ltc1690cms8#pbf

(Engineering Calculation)

MSOP

(printed on: 2020-07-11 21:42:54)

**TOTAL MASS (g) : 0.027354**

COMPONENT MATERIAL	VENDOR/ INDUSTRY NAMES	CONSTITUENT NAME	CAS NUMBER	CONSTITUENT MASS (g)	CONSTITUENT (PPM) OF MATERIAL	CONSTITUENT (PPM) OF TOTAL PKG.		
Active Device	Linear Technology	Silicon (Si)	7440-21-3	0.002069	1000000	75637.8515625		
Die Coat	Dow Corning	Silicone	69430-27-9	0.000000	0	0		
Lead Frame	Cu	Copper (Cu)	7440-50-8	0.010433	975000	381406.375		
		Iron (Fe)	7439-89-6	0.000257	24000	9395.32617188		
		Phosphorus (P)	7723-14-0	0.000003	300	109.673072815		
		Zinc (Zn)	7440-66-6	0.000007	700	255.903839111		
		Nickel (Ni)	7440-02-0	0.000000	0	0		
		Silicon (Si)	7440-21-3	0.000000	0	0		
		Magnesium (Mg)	7439-95-4	0.000000	0	0		
		Tin (Sn)	7440-31-5	0.000000	0	0		
<b>Lead Frame Total:</b>				<b>0.010700</b>	<b>1000000</b>	<b>391167.28125</b>		
Plating	PMI	Exter. Plating Pb	7439-92-1	0.000000	0	0		
		Exter. Plating Sn	7440-31-5	0.000710	1000000	25956.8730469		
		<b>External Plating Total:</b>				<b>0.000710</b>	<b>1000000</b>	<b>25956.8730469</b>
		Inter. Plating Ni	7440-02-0	0.000000	0	0		
		Inter. Plating Ag	7440-22-4	0.000086	1000000	3143.96142578		
<b>Internal Plating Total:</b>				<b>0.000086</b>	<b>1000000</b>	<b>3143.96142578</b>		
Die Attach	ELECTRICALLY CONDUCTIVE ADHESIVE	Silver (Ag)	7440-22-4	0.000704	750000	25736.6132812		
		Tin (Sn)	7440-31-5	0.000000	0	0		
		Lead (Pb)	7439-92-1	0.000000	0	0		
		Silica (SiO2)	60676-86-0	0.000000	0	0		
		Indium (In)	7440-74-6	0.000000	0	0		
		Metal Oxide		0.000000	0	0		
		Antimony (Sb)	7440-36-0	0.000000	0	0		
		Resin (EP)		0.000235	250000	8591.05664062		
<b>Die Attach Total:</b>				<b>0.000939</b>	<b>1000000</b>	<b>34327.671875</b>		
Encapsulation	MULTI-AROMATIC RESIN Br/Sb FREE	Resin (EP)		0.001659	130000	60649.203125		
		Bromine (Br)	40039-93-8	0.000000	0	0		
		Silica (SiO2)	60676-86-0	0.010591	830000	387182.5		
		Antimony Trioxide (Sb2O3)	1309-64-4	0.000000	0	0		
		Metal Hydroxide		0.000447	35000	16341.2880859		
		Carbon Black (C)	1333-86-4	0.000064	5000	2339.69213867		
		<b>Encapsulation Total:</b>				<b>0.012761</b>	<b>1000000</b>	<b>466512.65625</b>
Bond Wire Estimated	AFW/TANAKA/ Kn	Gold (Au)	7440-57-5	0.000089	1000000	3253.63427734		
					<b>TOTAL MASS (g) :</b>	<b>0.027354</b>		