© Copyrig	l Composition De ht 2005. IPC, Bannockl al and Pan-American co	burn, Illinois. A	ll rights reserved u ntions.	nder both	This docume level parts, t	ent is a declarat	ion of the spencompasse	ubstances v s all lower	within the manufactur level materials for w	er listed in hich the m	em. Note: if aanufacturer	the item is an as has engineering	ssembly with lower responsibility.	
	IPC Web Site for Information on IPC-1752 Standard Form Type http://www.ipc.org/IPC-175x Distribute				*	* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materi					als and Mfg Information			
Supplier Information														
Company name*			Company unique ID			Unique ID Authority				Response Date*				
onsemi										2023-06-08				
Contact Name Title -			Title - Contact			Phone - Contact*				Email - Contact*				
Product-Env-Stewards	Product Envi	Product Enviro Compliance			NA				Product-Env-Stewards@onsemi.com					
Authorized Representative* Tit			Title - Representative			Phone - Representative*			Email - Representative*					
Product-Env-Stewards	Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com					
Requester Item Number	uester Item Number Mfr Item Num		Number Mfr Item Name			Effective Date	Version	Ν	Ianufacturing Site		Weight*	UOM	Unit Type	
	74LVX2	74LVX245MX OCTAL TRA		NSCEIVER (3V)		2023-06-08		Т	TAD		535.9996	mg	Each	
Manufacturing Proccess I	nformation							I		ł				
Terminal Plating / Grid Array Material Terminal Base A		Alloy J	-STD-020 MSI	L Rating	Peak Proc	ess Body T	emperatur	e Max Time at Peak	Temperat	ure Numbe	er of Reflow Cy	cles		
Matte Tin (Sn) - annealed CU Alloy		CU Alloy	1	1		260		С	30	secon	ds 3			
Comments														
evel 1 - maximum time at peak t	emperature during so	ldering is 10-3	0 seconds											
For more information regarding	material composition	please refer to	page 3											

RoHS Material Composition Declaration				Declaration Type *	Detailed						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU	(Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).										
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe v others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and co for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of						
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	on above	Supplier Acceptance	* Accepted							
Exemption: If the declared item does not con applicable exemptions.	ntain RoHS restricted substances per	the definition above	except for defined RoHS exempti	ons, then select the corresponding response i	n the RoHS Declaration above and choose all						
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the						
Supplier Digital Signature Ra	stislav Drska	Le									

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

sigma range of distribution unless otherwise noted).									
Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure	
Die	25.835	mg	Supplier	Silicon (Si)	7440-21-3		25.835	mg	
Die Attach	0.4286	mg	Supplier	Silver (Ag)	7440-22-4		0.3107	mg	
			Supplier	Phenolic Resin-2	54208-63-8		0.1179	mg	
Lead Frame	171.52	mg	Supplier	Silver (Ag)	7440-22-4		1.372	mg	
			Supplier	Zinc (Zn)	7440-66-6		0.257	mg	
			Supplier	Iron (Fe)	7439-89-6		3.911	mg	
			Supplier	Copper (Cu)	7440-50-8		165.808	mg	
			Supplier	Phosphorus (P)	7723-14-0		0.172	mg	
Mold Compound-Black	321.6	mg	Supplier	Ortho Cresol Novolac Resin	29690-82-2		19.296	mg	
			Supplier	Carbon Black (C)	1333-86-4		3.216	mg	
			Supplier	Fused Silica (SiO2)	60676-86-0		289.44	mg	
			Supplier	Phenolic Resin (Novolac)	9003-35-4		9.648	mg	
Plating	16.08	mg	Supplier	Tin (Sn)	7440-31-5		16.08	mg	
Wire Bond - Au	0.536	mg	Supplier	Gold (Au)	7440-57-5		0.536	mg	

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).