	Material Comj © Copyright 2005. international and Pa	IPC, Bannockt	ourn, Illinois. A	Il rights reserved untions.	nder both	This docume level parts, t	ent is a declarat	ion of the s encompasse	ubstances es all lower	within the manufactur r level materials for w	rer listed i hich the r	tem. Note: i nanufacture	if the item is an as r has engineering	sembly with lower responsibility.	
1752-21.1	IPC Web Site for Information on IPC-1752 Standard Form Typ http://www.ipc.org/IPC-175x Distribute				* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materi				ials and M	als and Mfg Information					
Supplier	r Information														
Company name* C			Company un	Company unique ID			Unique ID Authority				Response Date*				
onsemi											2023-06	2023-06-08			
Contact N	ame	Title - Contact				Phone - Contact*				Email -	Email - Contact*				
Product-Env-Stewards			Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com				
Authorize	d Representative*	Title - Representative				Phone - Representative*				Email - Representative*					
Product-H	Env-Stewards	Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com					
	Requester Item Number Mfr Item		n Number Mfr Item Name				Effective Date	ate Version Manufacturing Site			Weight*	UOM	Unit Type		
		SVC276-TL-E FM Varicap		FM Varicap Twin	win VR 8V		2023-06-08		C	CNG		7.33	mg	Each	
Manufa	cturing Proccess Inform:	ation													
	Terminal Plating / Grid Array Material Te		erminal Base Alloy J-STD-020 MS		L Rating	Peak Process Body Temperate		'emperatur	ture Max Time at Peak Tempe		ture Numl	per of Reflow Cy	eles		
contains Bi CU Alle			CU Alloy	oy 1			260 C 30			seconds 3					
Comments															
level 1 - m	aximum time at peak temperat	ture during so	Idering is 10-3	0 seconds											
For more i	information regarding materia	l composition	please refer to	page 3											

RoHS Material Composition Declaration				Declaration Type *	Detailed						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU											
cadmium, hexavalentchromium, polybromina contains a RoHS restricted substance inexces encompass all such components. Supplier cer as of the date that Supplier completes this for Company acknowledges that Supplier may h independently verified information provided certification in this paragraph. If the Company	ated biphenyls and/or polybrominated dip s of an applicable quantity limit, please in iffies that it gathered the information it pr m.Supplier acknowledges that Company ave relied on informationprovided by oth by others, Supplier agrees that, at a minir and the Supplier enter into a written agr esource of the Supplier's liability and the	henyl ethers (each a "RoHS restricted substa ndicate below which, if any, RoHS exemption ovides in this form using appropriate methoo will rely on this certification in determining ers in completing this form, and that Supplie num, itssuppliers have provided certification eement with respect to the identified part, the Company's remedies for issues that arise reg	nce") in exco n you believe ls to ensure i the compliar r may not ha s regarding t terms and co	e may apply. If the part is an assembly with low s accuracy and that such information is true an ce of its products with European Union member de independently verified such information. Ho neir contributions to the part, and those certifica	ove. If a homogeneous material within the part er level components, the declaration shall d correct to the best of its knowledge and belief, er state laws that implement the RoHS Directive. wever, in situations where Supplier has not ations are at least as comprehensive as the anty rights and/or remedies provided as part of						
RoHS Declaration * 4 - Item(	s) does not contain RoHS restricted subst	ances per the definition above except for sele	ected exempt	ions Supplier Acceptance	* Accepted						
Exemption: 7a: Lead in high melting temperature type solders (i.e. lead based solder alloys containing 85% by weight or more lead).											
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
Instructions: Complete all of the required fields on all pages of this form. Select the "Accepted" on the Supplier Acceptance drop-down. This will display the signature area. Digitally sign the declaration (if required by the Requester) and click on Submit Form to have the form returned to the Requester.											
Supplier Digital Signature	astislav Drska	Le									

## Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	0.15	mg	Supplier	Silicon (Si)	7440-21-3		0.15	mg
Die Attach Solder	0.07	mg	Supplier	Silver (Ag)	7440-22-4		0.0018	mg
			А	Lead (Pb)	7439-92-1	7a	0.0648	mg
			Supplier	Tin (Sn)	7440-31-5		0.0035	mg
Lead Frame	2.79	mg	Supplier	Silver (Ag)	7440-22-4		0.0778	mg
			Supplier	Zinc (Zn)	7440-66-6		0.0053	mg
			В	Nickel (Ni)	7440-02-0		0.0131	mg
			Supplier	Iron (Fe)	7439-89-6		0.07	mg
			Supplier	Copper (Cu)	7440-50-8		2.6198	mg
			Supplier	Phosphorus (P)	7723-14-0		0.0039	mg
Mold Compound-Black	4.24	mg		Brominated epoxy resin	proprietary data		0.0848	mg
			Supplier	Epoxy Phenol Resin	Proprietary Data		0.0424	mg
			В	Antimony Trioxide (Sb2O3)	1309-64-4		0.0848	mg
			Supplier	Carbon Black (C)	1333-86-4		0.0424	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		3.2351	mg
			Supplier	Ortho-Cresol Novolac Resin	29690-82-2		0.742	mg
			Supplier	Silica Crystalline (SiO2)	14808-60-7		0.0085	mg
Plating	0.05	mg	В	Bismuth (Bi)	7440-69-9		0.0003	mg
			Supplier	Tin (Sn)	7440-31-5		0.0497	mg
Wire Bond - Au	0.03	mg	Supplier	Gold (Au)	7440-57-5		0.03	mg

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).