	Material Composition Declaration © Copyright 2005. IPC, Bannockburn, Illinois. All rights reser international and Pan-American copyright conventions.			All rights reserved untions.	under both	This document is a declaration of the substances within the manufa level parts, the declaration encompasses all lower level materials fo					urer listed item. Note: if the item is an assembly with lower which the manufacturer has engineering responsibility.				
1752-21.1	IPC Web Site for Information on IPC-1752 Standard Form Typ http://www.ipc.org/IPC-175x Distribute				* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materi					rials and N	als and Mfg Information				
Supplie	r Information														
Company name* Company un				unique ID			Unique ID Authority				Respon	Response Date*			
onsemi											2023-0	2023-06-08			
Contact N	lame		Title - Contact]	Phone - Contact*				Email ·	Email - Contact*			
Product-l	Env-Stewards		Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com				
uthorize	ed Representative*		Title - Representative]	Phone - Representative*				Email ·	Email - Representative*			
Product-l	Env-Stewards		Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com				
			n Number Mfr Item Name				Effective Date	Version	N	Ianufacturing Site		Weight*	UOM	Unit Type	
			Power Switcher	 21		2023-06-08	023-06-08 CPA		PA	A 2		mg	Each		
/anufa	cturing Proccess Informat	tion													
	Terminal Plating / Grid Array Material		Ferminal Base Alloy J-STD-020 M		J-STD-020 MSI	L Rating	Peak Process Body Temperat		mperatur	ure Max Time at Peak Temp		ture Number	of Reflow Cy	cles	
Matte Tin (Sn) - annealed		CU Alloy NA			0 C 30		30	seco	seconds 3						
omments	3														
or more	information regarding material	composition	please refer to	page 3											

RoHS Material Composition Declaration				Declaration Type *	Detailed							
Directive 2015/863/EU amending RoHS Directive 2011/65/EU												
cadmium, hexavalentchromium, polybromina contains a RoHS restricted substance inexces encompass all such components. Supplier cer as of the date that Supplier completes this for Company acknowledges that Supplier may h independently verified information provided certification in this paragraph. If the Company	ated biphenyls and/or polybrominated dip s of an applicable quantity limit, please in iffies that it gathered the information it pr m.Supplier acknowledges that Company ave relied on informationprovided by oth by others, Supplier agrees that, at a minir and the Supplier enter into a written agr esource of the Supplier's liability and the	henyl ethers (each a "RoHS restricted substa ndicate below which, if any, RoHS exemption ovides in this form using appropriate methoo will rely on this certification in determining ers in completing this form, and that Supplie num, itssuppliers have provided certification eement with respect to the identified part, the Company's remedies for issues that arise reg	nce") in exco n you believe ls to ensure i the compliar r may not ha s regarding t terms and co	e may apply. If the part is an assembly with low s accuracy and that such information is true an ce of its products with European Union member de independently verified such information. Ho neir contributions to the part, and those certifica	ove. If a homogeneous material within the part er level components, the declaration shall d correct to the best of its knowledge and belief, er state laws that implement the RoHS Directive. wever, in situations where Supplier has not ations are at least as comprehensive as the anty rights and/or remedies provided as part of							
RoHS Declaration * 4 - Item(s) does not contain RoHS restricted subst	ances per the definition above except for sele	ected exempt	ions Supplier Acceptance	* Accepted							
Exemption: 7a: Lead in high melting temperature type solders (i.e. lead based solder alloys containing 85% by weight or more lead).												
Exemption List Version	EL-2011/534/EU											
Declaration Signature												
Instructions: Complete all of the required fields on all pages of this form. Select the "Accepted" on the Supplier Acceptance drop-down. This will display the signature area. Digitally sign the declaration (if required by the Requester) and click on Submit Form to have the form returned to the Requester.												
Supplier Digital Signature	astislav Drska	Le										

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

sigma range of distribution unless otherwise noted).									
Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure	
Die	6.19	mg	Supplier	Silicon (Si)	7440-21-3		6.19	mg	
Die Attach	1.84	mg	Supplier	Silver (Ag)	7440-22-4		0.0276	mg	
			А	Lead (Pb)	7439-92-1	7a	1.7204	mg	
			Supplier	Tin (Sn)	7440-31-5		0.092	mg	
Lead Frame	1545.11	mg	Supplier	Silver (Ag)	7440-22-4		3.1007	mg	
			Supplier	Iron (Fe)	7439-89-6		1.5503	mg	
			Supplier	Copper (Cu)	7440-50-8		1539.9956	mg	
			Supplier	Phosphorus (P)	7723-14-0		0.4633	mg	
Mold Compound-Black	953.4	mg	Supplier	2,6-dibromo-4-[1-(3-bromo-4- hydroxyphenyl)-1-methylethyl]phenol	6386-73-8		28.6	mg	
			Supplier	Ortho Cresol Novolac Resin	29690-82-2		191.0003	mg	
			В	Antimony Trioxide (Sb2O3)	1309-64-4		23.8	mg	
			Supplier	Carbon Black (C)	1333-86-4		9.534	mg	
			Supplier	Fused Silica (SiO2)	60676-86-0		700.4656	mg	
Plating	21.6	mg	Supplier	Tin (Sn)	7440-31-5		21.6	mg	
Wire Bond - Cu	0.2084	mg	Supplier	Copper (Cu)	7440-50-8		0.2084	mg	

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).