



CUSTOMER TERMINAL	RoHS	LEAD(Pb)-FREE
Sn96%, Ag4%	Yes	Yes



ELECTRICAL SPECIFICATIONS @ 25°C unless otherwise noted:

PARAMETER	TEST CONDITIONS	VALUE
⑥D⑥B D.C. RESISTANCE	1-3 @20°C	0.35 ohms max.
⑥D D.C. RESISTANCE	6-4 @20°C	0.50 ohms max.
INDUCTANCE	1-3 10kHz, 100mVAC, Ls	475uH min.
⑥B INTERWINDING CAPACITANCE	1-6 100kHz, 10mVAC, Cs	17.5pF typ.
DIELECTRIC	1-6 3125VAC, 1 second	2500VAC, 1 minute
URNS RATIO	(6-4):(1-3)	1.7:1, ±2%

- ⑥F⑥B GENERAL SPECIFICATIONS:
 OPERATING TEMPERATURE RANGE: -40°C to +125°C including temp rise.
- ⑥F CURRENT RATING: 350mAAC
 VOLTAGE-TIME: 11VuS
- ⑥B Designed to comply with the following requirements as defined by IEC60950-1, EN60950-1, UL60950-1/CSA60950-1 and AS/NZS60950.1:
 - Functional insulation for a primary circuit at a working voltage of 400Vrms.
- ⑥E Qualified to AEC-Q200.



Wire insulation & RoHS status not affected by wire color.
 Wire insulation color may vary depending on availability.

⑥D

AGENCY NUMBER	
UL CODE FILE# E205930	CH
UL60950-1	E205930
CSA60950-1 (Via CUL)	E205930

REV.	DATE	Packaging Specifications
6H	4/21	Method: Tape & Reel
6G	12/20	PKG-0895
6F	6/18	www.we-online.com/midcom
6E	6/16	SEE REVISION SHEET FOR REVISION LEVEL

Tolerances unless otherwise specified:
 Angles: ±1° Decimals: ±.005 [0.13]
 Fractions: ±1/64 Footprint: ±.005 [0.13]

This drawing is dual dimensioned. Dimensions in brackets are in millimeters.

DRAWING TITLE
TRANSFORMER

eiSos p/n: 760390013

PART NO.
760390013

SPECIFICATION SHEET 1 OF 1